



- NOTE;
1. Material  
Barrel & Plunger: Brass C3604  
Spring: SUS304 Insulation coating
  2. Plating  
Plunger: 10 microinch Min. Au over 60~100 microinch Ni  
Barrel: 4 microinch Min. Au over 60~100 microinch Ni
  3. Electrical  
Rated current & voltage: DC 12V; 2A Max.  
Contact resistance: 30 mohm Max. at working height(quiescence)
  4. Mechanical  
Spring force: 100g±20g at working height(quiescence).  
Durability: 10,000 cycles(minimum)
  5. To ensure the best usage, please operate it based on the working height.
  6. RoHS and HF compliant.

		<b>深圳市鑫南天科技有限公司</b> Shen Zhen Xin Nan Tian Technology Co., Ltd			
		DIMENSIONS INIT: mm UNLESS OTHERWISE SPECIFIABLE DIMENSION TOLERANCE X.X: ± 0.25 X.XX: ± 0.20 X.XXX: ± 0.10 ANGULAR: ± 1°	PRODUCT NAME : POGO pin 2.00mm*10.00mm	DRAWING: COCO	DATE: 2014/04/26
		PRODUCT NO. : XNT-POGO-111138	CHECK: JANY	DATE: 2014/04/26	
		DRAWING NO. : XNT-1011	APPROVED: JEFF	DATE: 2014/04/26	
				SCALE: 1:1	
		DWG ID: P D	REV.: A	PAGE: 1 of 1	

REVISION NO.	ECR NO.	DESCRIPTION	MARK	DATE
1				
2				
3				